

HYBRID INVERTER CHARGER

VICTOR NM-ECO SERIES

120A MAX PV CHARGING

PURE SINE WAVE

WORKS WITH AND WITHOUT BATTERY

UPGRADED MPPT

LI-ION

BUILT IN ANTI DUST KIT

APP

WIFI&GPRS

LCD Display

RGB LIGHTS

Dual communication

DUSTPROOF

INVERTER MODE

PV MODE

UTILITY MODE

Features

- Pure sine wave solar inverter(on/off Grid)
- Output power factor 1.0
- WIFI&GPRS available for IOS and Android
- Inverter can run without battery
- One-key restoration to factory Settings
- Built-in Lithium battery automatic activation
- Dual communication ports for Battery communication and Wifi communication
- Built-in 120A MPPT Solar charge:max 6200W(for 3.6KW/4.2KW), max 6500W (for 6.2KW)
- High PV input voltage range(60~500VDC)
- Built-in anti-dust kit for harsh environment
- Smart battery charge design to optimize battery life
- Dual output

MODEL	VICTOR NM-ECO-3.6KW PLUS	VICTOR NM-ECO-4.2KW PLUS	VICTOR NM-ECO-6.2KW PLUS
Phase	1-phase		
Maximum PV Input Power	6200W	6200W	6500W
Rated Output Power	3600W/3600VA	4200W/4200VA	6200W/6200VA
Maximum Solar Charging Current	120A		

GRID-TIE OPERATION

PV INPUT (DC)

Nominal DC Voltage/Maximum DC Voltage	360/500VDC		
Start-up Voltage / Initial Feeding Voltage	60VDC/90VDC		
MPPT Voltage Range	60~450VDC		
Maximum Input Current	1/18A		1/22A

GRID OUTPUT (AC)

Nominal Output Voltage	220/230/240VAC		
Output Voltage Range	195.5~253VAC		
Nominal Output Current	15.7A	18.2A	27.0A
Power Factor	>0.99		

EFFICIENCY

Maximum Conversion Efficiency (DC/AC)	98%		
---------------------------------------	-----	--	--

TWO LOAD OUTPUT POWER

Full Load	3600W	4200W	6200W
Maxium Main Load	3600W	4200W	6200W
Maxium Second Load (battery mode)	1200W	1400W	2067W
Maxium Load Cut Off Voltage	26VDC	26VDC	52VDC
Maxium Load Return Voltage	27VDC	27VDC	54VDC

OFF-GRID OPERATION

AC INPUT

AC Start-up Voltage / Auto Restart Voltage	120-140VAC/180VAC		
Acceptable Input Voltage Range	90-280VAC or 170-280VAC		
Frequency Range	49~51±1HZ		
Maximum AC Input Current	30A	30A	40A

PV INPUT (DC)

Nominal DC Voltage/Maximum DC Voltage	360/500VDC		
MPPT Voltage Range	60~450VDC		
Maximum Input Current	1/18A		1/22A

BATTERY MODE OUTPUT (AC)

Nominal Output Voltage	220/230/240VAC		
Output Waveform	Pure sine wave		
Efficiency (DC to AC)	94%		

BATTERY & CHARGER

Nominal DC Voltage	24VDC		
Maximum Solar Charging Current	120A	140A	120A
Maximum AC Charging Current	100A	100A	100A
Maximum Solar+AC Charging Current	120A	140A	120A

HYBRID OPERATION

PV INPUT (DC)

Nominal DC Voltage/Maximum DC Voltage	360/500VDC		
Start-up Voltage / Initial Feeding Voltage	90VDC/120VDC		
MPPT Voltage Range	60~450VDC		
Maximum Input Current	1/18A		1/22A

GRID OUTPUT (AC)

Nominal Output Voltage	220/230/240VAC		
Output Voltage Range	195.5~253VAC		
Nominal Output Current	15.7A	18.2A	27.0A

AC INPUT

AC Start-up Voltage / Auto Restart Voltage	120-140VAC/180VAC		
Acceptable Input Voltage Range	90-280VAC or 170-280VAC		
Maximum AC Input Current	30A	30A	40A
Maximum AC Charging Current	100A		

GENERAL

PHYSICAL

Dimension, D x W x H (mm)	420*350*110		
Carton Dimension, D X W X H (mm)	500*415*180		
Net Weight (kgs)	8.0	8.0	8.9
Gross Weight(kgs)	9.0	9.0	10.0

INTERACE

Communication Port	RS232/RS485/WIFI/GPRS/LITHIUM BATTERY		
--------------------	---------------------------------------	--	--

ENVIRONMENT

Humidity	5% to 95% Relative Humidity(Non condensing)		
Operating Temperature	-10°C 50°C		

STANDARD

Compliance Safety	CE		
-------------------	----	--	--