


SPECIFICATION

Model	RTC 1024	RTC 2024	RTC 3024	RTC 5024	RTC 2410	RTC 2420
Rated voltage	12V / 24V Auto Work					
Max load current	10A	20A	30A	50A	10A	20A
Input voltage range	12V-17V / 24V-34V					
Length≤1m charge loop drop	0.25V					
Length≤1m discharge loop drop	0.05V					
Over voltage protection	17V / 34V					
Full charge cut	13.7V / 27.4V					
Low voltage cut	10.5V-11V / 21V-22V					
Temperature compensation	-3mv/°C / cell					
Ambient temperature	-25°C to + 55°C					
No load loss	≤10mA					

PWM SOLAR CHARGE CONTROLLER



Headquarters - China

A: No.30 Yongshun Road, Zhulin Town, Jintan District, Changzhou, Jiangsu Province, China

China, 213241

T: +86 519-82983001 F: +86 519-82983000

W: www.restarsolar.com

E: info@restarsolar.com

Dubai office



A: Shop No.8, Al Waswasi Building, Nakheel Road, Satellite Market, P.O. BOX-39158, Deira Dubai-U.A.E.

T: +971 04 264 33 39

E: sales@restarsolar.com

PWM SOLAR CHARGE CONTROLLER RTC SERIES

Restar RTC series is common positive PWM charge controller with LCD display. It adopts the most advanced digital technique. The multiple load control modes enable it can be widely used in solar home system, traffic signal, solar street light, solar garden lamp, etc.



Features

Load overload protection

PV short circuit protection

Battery reverse polarity connection protection

Battery over voltage protection

LCD display design, dynamically displaying device's operating data and working condition

Intellectualized temperature compensation

Battery overheating protection

Load short circuit protection

