

# Three Phase PV String Inverter

## 30-60 kW



The Restar RT-T Series Three-phase string inverters are designed for commercial and power plant PV system applications, rating from 30kW to 60kW. All models with aluminum housing which is anodized, increasing durability and effectively prevents corrosion. Equipped with external inductors, ensure efficient heat dissipation, which significantly improves the reliability and extends the life of the inverters.

The inverter menu is activated by sensor touch buttons. Communication implements are via the Wi-Fi module (which can be changed to Ethernet / GPRS). Check the system status anytime and anywhere via online portal or APP.

<b>Max. 20A</b> MAX. 20A dc String Current Up To 20A	<b>Max. 1.5</b> PV OVERSIZE Max. 1.5 Time PV Oversize Input	<b>PROTECTION</b> Multiple Intelligent Protections	<b>ANTI-FLOW</b> Anti-Feed-in Function	<b>Wi-Fi</b> Wi-Fi Standard, Ethernet/GPRS Optional	<b>CONFIGURATION</b> Quick & Easy Config. via Wi-Fi	<b>MODBUS</b> MODBUS Communication Ready
--	--	--	---	---	---	--

- MPPT efficiency > 99.9%
- IP 68 Cooling Fan
- Intelligent Temperature Control System
- Type II DC & AC lightning protection
- Active and reactive power compensation, adjust power factor
- AC output 1.1x continuous operation

Technical Data	RT-T030KTL	RT-T036KTL	RT-T040KTL	RT-T050KTL	RT-T060KTL
<b>PV Input Data</b>					
Max. DC Power ( W )	45000	54000	60000	75000	90000
Max. DC Voltage ( V )	1100				
MPPT Voltage Range ( V )	200-1000				
Rated Input Voltage ( V )	620				
Start-up Voltage ( V )	200				
Max. Input Current ( A )	38x2	38x3	40x3	38x4	
Max. Short Current ( A )	48x2	48x3	48x3	48x4	
No. of MPP Tracker / No. of PV String	2/5	3/6	3/7	4/8	
Input Connector Type	MC4				
<b>AC Output Data</b>					
Max. Output Power ( VA )	33000	39600	44000	55000	66000
Nominal Output Power ( W )	30000	36000	40000	50000	60000
Max. Output Current ( A )	48	60	65	80	96
Nominal Output Voltage ( V )	3P+N+PE / 3P+PE 230/400				
Grid Voltage Range	260Vac-519Vac (according to local standard)				
Nominal Output Frequency ( Hz )	50/60				
Grid Frequency Range	45-55Hz/55-65Hz (according to local standard)				
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)				
Output Current THD	<3%				
<b>Efficiency</b>					
Max. Efficiency	98.50%	98.65%	98.65%	98.80%	99.00%
Euro Efficiency	98.10%	98.20%	98.25%	98.45%	98.50%
<b>Protection</b>					
PV Reverse Polarity Protection	YES				
PV Insulation Resistance Detection	YES				
AC Short Circuit Protection	YES				
AC Over Current Protection	YES				
AC Over Voltage Protection	YES				
An[ ]-Islanding Protection	YES				
Residual Current Detection	YES				
Over Temperature Protection	YES				
Integrated DC switch	YES				
Surge Protection	Integrated (Type II)				
Smart IV Curve Scanning	YES				
Quick Arc Fault Circuit Interruption	Optional				
<b>General Data</b>					
Dimensions ( W x H x D, mm )	450 x 485 x 210	710 x 470 x 236			
Weight ( kg )	26	44	51		
Protection Degree	IP66				
Enclosure Material	Aluminum				
Ambient Temperature Range ( °C )	-25 to 60				
Humidity Range	0-100%				
Topology	Transformerless				
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional) / Sunspec				
Cooling Concept	Intelligent Fan Cooling				
Night Power Consumption ( W )	<1				
Max. Operation Altitude ( m )	≤4000				
<b>Certifications and Standards</b>					
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-11, EN61000-3-12				
Safety Standard	UL1741, EN62109				
Grid-connection	IEEE1547, CSA C22, EN50549, RD1699, PORTARIA N° 140+515, G99, IEC61727				