

## LED SPECIFICATION RTL series

RTL led bulb light feature

challenge the limit to save power



More save  
electricity



Longer  
service life



More  
Secure



More  
reduction



## Component characteristics



supper long life, Non-UV and energy saving




Amazing design with aluminum inside, high quality plastic outside



Green and Eco-friendly



Safe and well heat dissipation



PC cover light transmittance is above 90%



| MODEL NO.         | RTL03                             | RTL05 | RTL07 | RTL09          | RTL12 | RTL15  |
|-------------------|-----------------------------------|-------|-------|----------------|-------|--------|
| VOLTAGE           | AC: 220-240V                      |       |       |                |       |        |
| BEAM ANGLE        | 270                               |       |       |                |       |        |
| LED TYPE          | SMD2835                           |       |       |                |       |        |
| Ra                | >80                               |       |       |                |       |        |
| LUMEN             | 240LM                             | 400LM | 560LM | 720LM          | 840LM | 1050LM |
| COLOR TEMPERATURE | 6500K                             |       |       |                |       |        |
| MATERIAL          | Heart conductive plastic+Aluminum |       |       |                |       |        |
| DIMENSON          | 110(L)*60(D)MM                    |       |       | 120(L)*60(D)MM |       |        |

## LED SPECIFICATION RTL series

RTL led bulb light feature

challenge the limit to save power



More save  
electricity



Longer  
service life



More  
Secure



More  
reduction



## Component characteristics



supper long life, Non-UV and energy saving




Amazing design with aluminum inside, high quality plastic outside



Green and Eco-friendly



Safe and well heat dissipation



PC cover light transmittance is above 90%

| MODEL NO.         | RTL03                             | RTL05 | RTL07 | RTL09          | RTL12 | RTL15  |
|-------------------|-----------------------------------|-------|-------|----------------|-------|--------|
| VOLTAGE           | AC: 220-240V                      |       |       |                |       |        |
| BEAM ANGLE        | 270                               |       |       |                |       |        |
| LED TYPE          | SMD2835                           |       |       |                |       |        |
| Ra                | >80                               |       |       |                |       |        |
| LUMEN             | 240LM                             | 400LM | 560LM | 720LM          | 840LM | 1050LM |
| COLOR TEMPERATURE | 6500K                             |       |       |                |       |        |
| MATERIAL          | Heart conductive plastic+Aluminum |       |       |                |       |        |
| DIMENSON          | 110(L)*60(D)MM                    |       |       | 120(L)*60(D)MM |       |        |