

Solar Home Refrigerator



BC-50
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 5 L
Temperature range 1-10 for fridge, <=-18 for freezer
Product size(mm) 480*445*500
Carton size(mm) 500*465*530
Loading qty in 40HQ 573
G.W(KG)/N.W(KG) 12/10
Refrigerant R134A/R600A



BC-70
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 6 L
Temperature range 1-10 for fridge, <=-18 for freezer
Product size(mm) 450*405*845
Carton size(mm) 465*425*870
Loading qty in 40HQ 414
G.W(KG)/N.W(KG) 17/15
Refrigerant R134A/R600A



BC-90
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 8 L
Temperature range 1-10 for fridge, <=-18 for freezer
Product size(mm) 480*445*845
Carton size(mm) 500*465*870
Loading qty in 40HQ 352
G.W(KG)/N.W(KG) 22/20
Refrigerant R134A/R600A



BCD-108
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 41 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 450*460*1250
Carton size(mm) 465*480*1305
Loading qty in 40HQ 240
G.W(N.W(KG)) 32/29
Refrigerant R134A/R600A



BCD-118
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 39 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 480*490*1105
Carton size(mm) 500*540*1160
Loading qty in 40HQ 184
G.W(KG)/N.W(KG) 31/28
Refrigerant R134A/R600A



BCD-142
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 39 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 480*490*1265
Carton size(mm) 500*540*1320
Loading qty in 40HQ 184
G.W(KG)/N.W(KG) 35/32
Refrigerant R134A/R600A



BCD-178
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 39 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 500*565*1290
Carton size(mm) 535*620*1340
Loading qty in 40HQ 160
G.W(KG)/N.W(KG) 41/37
Refrigerant R134A/R600A



BCD-198
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 80 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 520*550*1515
Carton size(mm) 560*600*1550
Loading qty in 40HQ 136
G.W(KG)/N.W(KG) 47/42
Refrigerant R134A/R600A

Solar Home Refrigerator



BCD-218
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 45 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 550*575*1390
Carton size(mm) 570*605*1450
Loading qty in 40HQ 142
G.W(KG)/N.W(KG) 45/40
Refrigerant R134A/R600A



BCD-268
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 55 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 550*570*1619
Carton size(mm) 570*600*1680
Loading qty in 40HQ 106
G.W(KG)/N.W(KG) 50/45
Refrigerant R134A/R600A



BCD-168
Input voltage(V) 12V/24V/220V
Capacity(freezer room) 57 L
Temperature range 0-10 for fridge, <=-18 for freezer
Product size(mm) 500*560*1300
Carton size(mm) 535*620*1340
Loading qty in 40HQ 160
G.W(KG)/N.W(KG) 45/42
Refrigerant R134A/R600A



BCD-270
Input voltage(V) 12V/24V/220V
Capacity (freezer room) 124L
Temperature range 0-10 for fridge, <=-18 for freezer
Production sizes(mm) 580*590*1660
Carton Size (mm) 630*635*1720
Loading qty in 40HQ 77
G.W(KG)/N.W(KG) 56/61
Refrigerant R134A /600A



BCD-288
Input voltage(V) 12V/24V/220V
Capacity (freezer room) 75L
Temperature range 0-10 for fridge, <=-18 for freezer
Production sizes(mm) 606*680*1520
Carton Size (mm) 625*735*1575
Loading qty in 40HQ 79
G.W(KG)/N.W(KG) 60/54
Refrigerant 600A



BCD-298
Input voltage(V) 12V/24V/220V
Capacity (freezer room) 68L
Temperature range 0-10 for fridge, <=-18 for freezer
Production sizes(mm) 595*695*1525
Carton Size (mm) 625*705*1575
Loading qty in 40HQ 92
G.W(KG)/N.W(KG) 64/60
Refrigerant 600A



BCD-338
Input voltage(V) 12V/24V/220V
Capacity (freezer room) 96L
Temperature range 0-10 for fridge, <=-18 for freezer
Production sizes(mm) 595*695*1855
Carton Size (mm) 650*735*1950
Loading qty in 40HQ 72
G.W(KG)/N.W(KG) 75/65
Refrigerant 600A

85 mm ThicknessFoaming Body Solar Chest Freezer with Curved Glass Door for Ice Cream

SD/SC-168Y
Capacity (litre) 168
Temp Control mechanical
Voltage (v) 12V/24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R134a
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 730*700*826MM
Packing Dimension(W*D*H)MM 785*755*882MM
G.W(KG)/N.W(KG) 38/35
Temperature <=-18°C
Qty/40HQ 132

SD/SC-268Y
Capacity (litre) 268
Temp Control mechanical
Voltage (v) 12V/24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R290
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1041*700*840MM
Packing Dimension(W*D*H)MM 1096*755*882MM
G.W(KG)/N.W(KG) 61/57
Temperature <=-18°C
Qty/40HQ 94

SD/SC-308Y
Capacity (litre) 308
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R290
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1250*700*840MM
Packing Dimension(W*D*H)MM 1305*755*882MM
G.W(KG)/N.W(KG) 70/65
Temperature <=-18°C
Qty/40HQ 81



SD/SC-368Y
Capacity (litre) 368
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R290
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1410*700*840MM
Packing Dimension(W*D*H)MM 1460*780*900MM
G.W(KG)/N.W(KG) 73/68
Temperature <=-18°C
Qty/40HQ 72

SD/SC-408Y
Capacity (litre) 408
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R134a
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1520*700*840MM
Packing Dimension(W*D*H)MM 1575*755*882MM
G.W(KG)/N.W(KG) 78/72
Temperature <=-18°C
Qty/40HQ 66

SD/SC-468Y
Capacity (litre) 468
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R134a
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1630*700*840MM
Packing Dimension(W*D*H)MM 1685*755*882MM
G.W(KG)/N.W(KG) 81/75
Temperature <=-18°C
Qty/40HQ 63

SD/SC-508Y
Capacity (litre) 508
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R134a
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1780*700*840MM
Packing Dimension(W*D*H)MM 1835*755*882MM
G.W(KG)/N.W(KG) 86/80
Temperature <=-18°C
Qty/40HQ 57

SD/SC-618Y
Capacity (litre) 618
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R290
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 1780*700*900MM
Packing Dimension(W*D*H)MM 1835*755*945MM
G.W(KG)/N.W(KG) 95/89
Temperature <=-18°C
Qty/40HQ 50

SD/SC-718Y
Capacity (litre) 718
Temp Control mechanical
Voltage (v) 24V/220V/50Hz
Basket one
Isolation Thickness 85mm
Refrigerant R290
Wheel 4
Color of Door Frame white
Key and Lock Yes
Glass 4mm
Outside Condenser Yes
Paper sticker Optional
Fan cooling Compressor Yes
Unit Dimension(W*D*H)MM 2000*700*900MM
Packing Dimension(W*D*H)MM 2055*755*945
G.W(KG)/N.W(KG) 105/99
Temperature <=-18°C
Qty/40HQ 45

110 mm ThicknessFoaming Body Solar Chest Freezer-Super Energy Save

BD/BC-68H
Power consumption 37W
Input voltage(w) DC12V/24V
capacity 68 Litre
Product size(mm) 670*661*640
Carton size(mm) 710*681*682
G.W(KG)/N.W(KG) 35/30
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Thermostat mechanical
Defrost white
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 153

BD/BC-88H
Power consumption 39W
Input voltage(w) DC12V/24V
capacity 88 Litre
Product size(mm) 840*661*640
Carton size(mm) 880*681*682
G.W(KG)/N.W(KG) 34/38
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 132



BD/BC-108H
Power consumption 47W
Input voltage(w) DC12V/24V
capacity 108 Litre
Product size(mm) 670*661*840
Carton size(mm) 710*681*882
G.W(KG)/N.W(KG) 41/36
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 153

BD/BC-158H
Power consumption 49W
Input voltage(w) DC12V/24V
capacity 158 Litre
Product size(mm) 840*661*840
Carton size(mm) 880*681*882
G.W(KG)/N.W(KG) 45/41
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 132

BD/BC-208H
Power consumption 68W
Input voltage(w) DC12V/24V
capacity 208 Litre
Product size(mm) 996*661*840
Carton size(mm) 1036*681*882
G.W(KG)/N.W(KG) 52/47
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 123

BD/BC-258H
Power consumption 78W
Input voltage(w) DC12V/24V
capacity 258 Litre
Product size(mm) 1038*745*840
Carton size(mm) 1078*765*882
G.W(KG)/N.W(KG) 55/50
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 99

BD/BC-358H
Power consumption 105W
Input voltage(w) DC12V/24V
capacity 358 Litre
Product size(mm) 1380*745*840
Carton size(mm) 1420*765*882
G.W(KG)/N.W(KG) 84/78
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 66

BD/BC-408H
Power consumption 110W
Input voltage(w) DC12V/24V
capacity 408 Litre
Product size(mm) 1566*806*840
Carton size(mm) 1606*815*882
G.W(KG)/N.W(KG) 88/83
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 52

BD/BC-508H
Power consumption 157W
Input voltage(w) DC12V/24V
capacity 508 Litre
Product size(mm) 1826*806*840
Carton size(mm) 1866*815*882
G.W(KG)/N.W(KG) 109/103
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 52

BD/BC-618H
Power consumption 165W
Input voltage(w) DC24V/220V/50Hz
capacity 618 Litre
Product size(mm) 1826*806*900
Carton size(mm) 1866*815*942
G.W(KG)/N.W(KG) 116/110
Temperature range <=-18 degree
Inner glass door key& lock yes
Inner light optional
Basket/pcs 1
Thermostat mechanical
Colour white
Defrost manual
Compressor/quantities 1
Doors/quantities 1
Loading quantity/40HQ 24