

65mm Thickness Foaming Body Solar Chest Freezer



BD/BC-68

Input voltage(w) capacity	DC12V/24V 68 Litre
Temperature range	<= -18 degree
Product size(mm)	585*555*640
Carton size(mm)	620*580*690
Loading quantity/40HQ	289
G.W(KG)/N.W(KG)	25/23
Refrigerant	R134A/R600A



BD/BC-88

Input voltage(w) capacity	DC12V/24V 88 Litre
Temperature range	<= -18 degree
Product size(mm)	750*555*640
Carton size(mm)	785*580*690
Loading quantity/40HQ	229
G.W(KG)/N.W(KG)	31/28
Refrigerant	R134A/R600A



BD/BC-308

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	308 Litre
Temperature range	<= -18 degree
Product size(mm)	1110*668*840
Carton size(mm)	1148*670*885
Loading qty in 40HQ	104
G.W(KG)/N.W(KG)	50/47
Refrigerant	R134A/R600A



BD/BC-408

Input voltage(V)	DC12V/24V/220V
Capacity	408Litre
Temperature range	<= -18 degree
Product size(mm)	1410*745*840
Carton size(mm)	1465*755*885
Loading quantity/40HQ	72
G.W(KG)/N.W(KG)	63/60
Refrigerant	R134a/600A



BD/BC-268

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	268 Litre
Temperature range	<= -18 degree
Product size(mm)	1090*585*842
Carton size(mm)	1120*610*880
Loading qty in 40HQ	118
G.W(KG)/N.W(KG)	46/42
Refrigerant	R134A/R600A



BD/BC-358

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	358 Litre
Temperature range	<= -18 degree
Product size(mm)	1294*645*840
Carton size(mm)	1335*665*882
Loading qty in 40HQ	81
G.W(KG)/N.W(KG)	56/52
Refrigerant	R134A/R600A



BD/BC-508

Input voltage(V)	DC12V/24V
Capacity	508Litre
Temperature range	<= -18 degree
Product size(mm)	1525*675*870
Carton size(mm)	1575*755*885
Loading quantity/40HQ	65
G.W(KG)/N.W(KG)	67/61
Refrigerant	R134A/600A



BD/BC-158

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	158 Litre
Temperature range	<= -18 degree
Product size(mm)	750*555*840
Carton size(mm)	790*580*885
Loading qty in 40HQ	180
G.W/N.W(KG)	35/32
Refrigerant	R134A/R600A




BD/BC-208

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	208 Litre
Temperature range	<= -18 degree
Product size(mm)	906*555*840
Carton size(mm)	946*580*885
Loading qty in 40HQ	148
G.W/N.W(KG)	39/36
Refrigerant	R134A/R600A



BD/BC-258

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	258 Litre
Temperature range	<= -18 degree
Product size(mm)	952*668*840
Carton size(mm)	990*680*855
Loading qty in 40HQ	125
G.W(KG)/N.W(KG)	44/40
Refrigerant	R134A/R600A



BCD-258D

Power consumption	80W
Input voltage(w) capacity	12V/24V 220V50Hz 258 Litre(149Litre FREEZER+ 109Litre FRIDGE)
Product size(mm)	1075*585*840
Carton size(mm)	1120*610*880
G.W(KG)/N.W(KG)	45.8/42
Temperature range	0-10 / <= -18 degree
Inner glass door	yes
key& lock	yes
Inner light	Optional
Basket/pcs	1
Thermostat	Digital
Doors/quantities	2
Loading quantity/40HQ	118

BCD-338D

Power consumption	100W
Input voltage(w) capacity	12V/24V 220V50Hz 338 Litre(195LitreFREEZER+ 143LitreFRIDGE)
Product size(mm)	1294*645*840
Carton size(mm)	1335*665*882
G.W(KG)/N.W(KG)	71/68
Temperature range	0-10 / <= -18 degree
Inner glass door	yes
key& lock	yes
Inner light	Optional
Basket/pcs	1
Thermostat	Digital
Doors/quantities	2
Loading quantity/40HQ	81

BD/BC-608

Input voltage(V)	DC12V/24V
Capacity	608Litre
Temperature range	<= -18 degree
Product size(mm)	1785*745*834
Carton size(mm)	1835*755*885
Loading quantity/40HQ	56
G.W(KG)/N.W(KG)	76/72
Refrigerant	R134A/600A

BD/BC-708

Input voltage(V)	DC24V
Capacity	708Litre
Temperature range	<= -18 degree
Product size(mm)	1785*795*890
Carton size(mm)	1835*895*965
Loading quantity/40HQ	26
G.W(KG)/N.W(KG)	91/86
Refrigerant	R134a/600A

BD/BC-1088

Input voltage(V)	DC24V
Capacity	1088Litre
Temperature range	<= -18 degree
Product size(mm)	2035*1020*930
Carton size(mm)	2095*1035*1010
Loading quantity/40HQ	22
G.W(KG)/N.W(KG)	130/125
Refrigerant	R134A/600A

BD/BC-1688

Input voltage(V)	DC24V
Capacity	1688Litre
Temperature range	<= -18 degree
Product size(mm)	3175*1025*950
Carton size(mm)	3235*1035*1020
Loading quantity/40HQ	12
N.W./G.W(KG)	176/182
Refrigerant	R134A/600A

BD/BC-658

Input voltage(V)	DC24V
Capacity	658Litre
Temperature range	<= -18 degree
Product size(mm)	1598*885*935
Carton size(mm)	1660*895*1010
Loading quantity/40HQ	28
G.W(KG)/N.W(KG)	87/82
Refrigerant	R134A/600A

BD/BC-798

Input voltage(V)	DC24V
Capacity	798Litre
Temperature range	<= -18 degree
Product size(mm)	1950*885*935
Carton size(mm)	2010*895*1010
Loading quantity/40HQ	24
G.W(KG)/N.W(KG)	112/106
Refrigerant	R134A/600A

BD/BC-1388

Input voltage(V)	DC24V
Capacity	1388Litre
Temperature range	<= -18 degree
Product size(mm)	2335*1025*930
Carton size(mm)	2395*1020*1010
Loading quantity/40HQ	16
G.W(KG)/N.W(KG)	157/152
Refrigerant	R134A/600A

Solar Upright Cooler



LC-138

Input voltage(V)	12V/24V/220V
Capacity	138 Liter
Temperature range	0-10degree
Product size(mm)	500*535*1300
Carton size(mm)	550*585*1340
Loading qty in 40HQ	166
G.W(KG)/N.W(KG)	45/42
Refrigerant	R134A/R600A

LC-188

Input voltage(V)	12V/24V/220V
Capacity	188 Liter
Temperature range	0-10 degree
Product size(mm)	500*535*1655
Carton size(mm)	550*585*1715
Loading qty in 40HQ	111
G.W(KG)/N.W(KG)	53/49
Refrigerant	R134A/R600A



LC-218

Input voltage(V)	12V/24V/220V
Capacity	218 Liter
Temperature range	0-10 degree
Product size(mm)	556*573*1720
Carton size(mm)	625*635*1795
Loading qty in 40HQ	76
G.W(KG)/N.W(KG)	68/55
Refrigerant	R134A/R600A

LC-268

Input voltage(V)	12V/24V/220V
Capacity	268 Liter
Temperature range	0-10 degree
Product size(mm)	556*573*1895
Carton size(mm)	625*645*1970
Loading qty in 40HQ	75
G.W(KG)/N.W(KG)	71/58
Refrigerant	R134A/R600A

LC-328

Input voltage(V)	12V/24V/220V
Capacity	300 Liter
Temperature range	0-10 degree
Product size(mm)	620*573*1895
Carton size(mm)	680*645*1970
Loading qty in 40HQ	72
G.W(KG)/N.W(KG)	75/62
Refrigerant	R134A/R600A



LC-428

Input voltage	24V 220V50Hz
Capacity litres	428
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	880*590*2000
Packing Dimension(W*D*H) mm	945*640*2090
G.W(KG)/N.W(KG)	98/89
Refrigerant	R290
Loading qty in 40HQ	43



LC-998

Input voltage	24V 220V50Hz
Capacity litres	998
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	1605*590*2000
Packing Dimension(W*D*H) mm	1665*640*2090
G.W(KG)/N.W(KG)	153/140
Refrigerant	R290
Loading qty in 40HQ	25

LC-658

Input voltage	24V 220V50Hz
Capacity litres	658
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	1070*590*2000
Packing Dimension(W*D*H) mm	1135*640*2090
G.W(KG)/N.W(KG)	123/110
Refrigerant	R290
Loading qty in 40HQ	36

Solar Ice Maker

BD-198-11



BD-198-7



BD-198-10 ROLL-BOND



BD-198

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	198 L
Temperature range	<= -18 for freezer
Product size(mm)	550*635*1410
Carton size(mm)	570*650*1465
Loading qty in 40HQ	123
G.W(KG)/N.W(KG)	52/49
Refrigerant	R134A/R600A

Solar Air Conditioner

KF-26GWS

Cooling Capacity	2600W / 0.75ton / 9000BTU
Input Power(W) -Cooling	650-720
Input voltage(V)	DC24V
Rated Current(A)-Cooling	13.5-15
Noise-Indoor-dB(A)	<=39
Noise-Outdoor-dB(A)	<=49
Air Circulation(M3/H)	470
Suitable Area(M2)	11-18
EER-W/W	3.84
EER-Btu/h/w	13.53
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	11/14
Outdoor Unit-Net/Gross(KGS)	33/38
Indoor Unit-Net(mm)	745*255*195
Indoor Unit-Shipping(mm)	780*240*305
Outdoor Unit-Net(mm)	645*245*495
Outdoor Unit-Shipping(mm)	725*320*540

KF-35GWS

Cooling Capacity	3500W / 1ton / 12000BTU
Input Power(W) -Cooling	800-950
Input voltage(V)	DC48V
Rated Current(A)-Cooling	16.7-19.1
Noise-Indoor-dB(A)	<=43
Noise-Outdoor-dB(A)	<=52
Air Circulation(M3/H)	570
Suitable Area(M2)	16-28
EER-W/W	4.23
EER-Btu/h/w	14.08
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	12/15
Outdoor Unit-Net/Gross(KGS)	35/40
Indoor Unit-Net(mm)	775*260*210
Indoor Unit-Shipping(mm)	840*325*265
Outdoor Unit-Net(mm)	790*260*540
Outdoor Unit-Shipping(mm)	910*370*610

KF-50GWS

Cooling Capacity	5000W / 1.5ton / 18000BTU
Input Power(W) -Cooling	890-1000
Input voltage(V)	DC48V
Rated Current(A)-Cooling	18.36-22.1
Noise-Indoor-dB(A)	<=43
Noise-Outdoor-dB(A)	<=52
Air Circulation(M3/H)	1000
Suitable Area(M2)	25-35
EER-W/W	5.38
EER-Btu/h/w	14.13
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	16.3/19.2
Outdoor Unit-Net/Gross(KGS)	63/67
Indoor Unit-Net(mm)	1070*385*265
Indoor Unit-Shipping(mm)	1100*400*285
Outdoor Unit-Net(mm)	850X290X580
Outdoor Unit-Shipping(mm)	995*390*650

KF-70GWS

Cooling Capacity	7000W / 2ton / 24000BTU
Input Power(W) -Cooling	1258-1325
Input voltage(V)	DC48V
Rated Current(A)-Cooling	24.92-26.89
Noise-Indoor-dB(A)	<=43
Noise-Outdoor-dB(A)	<=52
Air Circulation(M3/H)	1200
Suitable Area(M2)	35-45
EER-W/W	5.66
EER-Btu/h/w	14.37
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	20/22
Outdoor Unit-Net/Gross(KGS)	71/77
Indoor Unit-Net(mm)	1070*385*265
Indoor Unit-Shipping(mm)	1100*400*285
Outdoor Unit-Net(mm)	850X290X580
Outdoor Unit-Shipping(mm)	995*390*650