



>>> Features

- Pure sine wave solar inverter(on/off Grid)Output power factor 1.0
- WIFI&GPRS available for IOS and Android
- Inverter running without battery
- One-key restoration to factory Settings
- Built-in Lithium battery automatic activation
- Built-in 120A(for 3.6KW/6.2KW)
- MPPT:Max 6200W(for 3.6KW),Max 4200W(for 4.2KW),Max 6500W(for 6.2KW)solar charge
- High PV input voltage range(60~450VDC)
- Built-in anti-dusk kit for harsh environment
- Smart battery charge design to optimize battery life
- Dual output



» Product Data Sheet

MODEL	RT-HY 4.2KW	RT-HY 6.2KW
Phase	1-phase	
Maximum PV Input Power	6200W	6500W
Rated Output Power	4200W/4200VA	6200W/6200VA
Maximum Solar Charging Current	120A	
GRID-TIE OPERATION		
PV INPUT(DC)		
Nominal DC Voltage/Maximum DC Voltage	360/500VDC	
Start-up Voltage/Initial Feeding Voltage	60VDC/90VDC	
MPPT Voltage Range	60~450VDC	
Maximum Input Current	1/18A	1/22A
GRID OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	195~253VAC	
Nominal Output Current	18.2A	27.0A
Power Factor	>0.99	
EFFICIENCY		
Maximum Conversion Efficiency(DC / AC)	98%	
TWO LOAD OUTPUT POWER		
Full Load	4200W	6200W
Maximum Main Load	4200W	6200W
Second Load Range	840W~2940W	1240W~4340W
Maximum Load Cut Off Voltage	26VDC	52VDC
Maximum Load Return Voltage	27VDC	54VDC
OFF-GRID OPERATION		
AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140VAC/180VAC	
Acceptable Input Voltage Range	90~280VAC or 170~280VAC	
Frequency Range	50±1Hz/60±1Hz	
Maximum AC input Current	24.7A	36.4A
PV INPUT(DC)		
Nominal DC Voltage/Maximum DC Voltage	360/500VDC	
MPPT Voltage Range	60~450VDC	
Maximum Input Current	1/18A	1/22A
BATTERY MODE OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Output Wave Form	Pure sine wave	
Efficiency (DC to AC)	94%	
BATTERY&CHARGER		
Nominal DC Voltage	24VDC	48VDC
Maximum Solar Charging Current	120A	120A
Maximum AC Charging Current	100A	100A
Maximum Sotar+AC Charging Current	120A	120A
HYBRID OPERATION		
PV INPUT(DC)		
Nominal DC Voltage/Maximum DC Voltage	360/500VDC	
Start-up Voltage/Initial Feeding Voltage	90VDC/120VDC	
MPPT Voltage Range	60~450VDC	
Maximum Input Current	1/18A	1/22A
GRID OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	195~253VAC	
Nominal Output Current	18.2A	27.0A
AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140VAC/180VAC	
Acceptable Input Voltage Range	90-280VAC or 170-280VAC	
Maximum AC Input Current	24.7A	36.4A
Maximum Charging Current	100A	
GENERAL		
PHYSICAL		
Dimension ,H*W*D(mm)	420*350*110	
Cartoon Dimension ,H*W*D(mm)	500*415*180	
Net Weight (kgs)	8.0	8.9
Gross Weight(kgs)	9.0	10.0
INTERACE		
Communication Port	RS232/RS485/WIFI/GPRS/LITHIUM BATTERY	
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non~condensing)	
Operating Temperature	-10℃~50℃	
STANDARD		
Compliance Safety	CE	

or more information , visit / contact us at www.restarsolar.com