

Three Phase Hybrid Storage Inverter

3-30 kW



The Afore AF series three phase storage inverters are designed to increase energy independence for homeowners and commercial users. The power range is from 3.0kW to 30kW, compatible with high voltage (150-800V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.

AI EMS
Electricity Pricing & Automation

BATTERY
Support Sodium metal chloride battery

WIDE RANGE
Voltage Range (150-800V)

100% UNBALANCE
Support Unbalance Load

Max. 40A
String Current Up To 40A

UPS FUNCTION
Switch Time < 10ms

INPUT
Support Generator

Support for Time-of-use Optimization

Configurable Operation Modes


AFCI (Optional) & Rapid Shutdown Ready

Build in Anti-feed-in Function


100% unbalanced output, each phase;
200% unbalanced output, each phase (≤ 10kW)

Smart Monitoring & Remote Firmware Upgrade

For New Storage System:




Optimizing Self-Consumption (on-grid) + Emergency Power Supply (off-grid)



Optimizing Self-Consumption Mode

With energy storage system installed, users may also be able to change from a flat rate electricity tariff to a time-of-use tariff. For the areas and regions, where peak shaving can be applied.



Technical Data	AF3K-TH	AF4K-TH	AF5K-TH	AF6K-TH	AF8K-TH	AF10K-TH
PV Input						
Max. DC Input Power (kW)	5	6	7.5	9	12	15
Max. PV Voltage (V)	1000					
Rated DC Input Voltage (V)	620					
DC Input Voltage Range (V)	150-1000					
MPPT Voltage Range (V)	150-850					
Full MPPT Range(V)	200-850			250-850	300-850	500-850
Start-up Voltage (V)	160					
Max. DC Input Current (A)	20x2					
Max. Short Current(A)	30x2					
No. of MPPT Tracker / Strings	2/2					
Battery Port						
Battery Nominal Voltage (V)	200	200	200	250	300	400
Battery Voltage Range (V)	150-800					
Max. Charge/Discharge Current (A)	30					
Max. Charge/Discharge Power (kW)	3	4	5	6	8	10
Charging Curve	3 Stages					
Compatible Battery Type	Li-ion / Lead-acid / Sodium metal chloride battery					
AC Grid						
Nominal AC Output Power (kW)	3	4	5	6	8	10
Max. AC Input/Output Power (kVA)	4.5 / 3.3	6 / 4.4	7.5 / 5.5	9 / 6.6	12 / 8.8	15 / 11
Max. AC Output Current (A)	5.3	7	8.5	10.5	13.5	17
Nominal AC Voltage (V)	230/400					
Nominal AC Frenquency (Hz)	50/60					
Power Factor	1 (-0.8-0.8 adjustable)					
Current THD (%)	<3 %					
AC Load Output (Back-up)						
Nominal Output Power (kVA)	3	4	5	6	8	10
Nominal Output Voltage (V)	230/400					
Nominal Output Frequency (Hz)	50/60					
Nominal Output Current (A)	4.4	5.8	7.3	8.7	11.6	14.5
Peak Output Power	3.3kVA, 60s	4.4kVA, 60s	5.5kVA, 60s	6.6kVA, 60s	8.8kVA, 60s	11kVA, 60s
THDV (with linear load)	<3 %					
Switching Time (ms)	<10					
Efficiency						
Europe Efficiency	97.50 %					
Max. Efficiency	98.00 %				98.20 %	
Battery Charge/Discharge Efficiency	98.00 %					
Protection						
Reverse Polarity Protection	Yes					
Over Current / Voltage Protection	Yes					
Anti-islanding Protection	Yes					
AC Short-circuit Protection	Yes					
Leakage Current Detection	Yes					
Ground Fault Monitoring	Yes					
Grid Monitoring	Yes					
Enclosure Protect Level	IP65					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	558 x 535 x 260 mm					
Weight (kg)	29kg					
Topology	Transformerless					
Cooling Concept	Natural Convection				Intelligent Fan	
Relatively Humidity	0-100 %					
Operating Temperature Range (°C)	-25 to 60 °C					
Operating Altitude (m)	<4000					
Standby Consumption (W)	<5					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	NRS097, G98, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1					
EMC	EN61000-6-2, EN61000-6-3					

Technical Data	AF12K-TH	AF15K-TH	AF17K-TH	AF20K-TH	AF25K-TH	AF30K-TH
PV Input						
Max. DC Input Power (kW)	18	22.5	25.5	30	37.5	45
Max. PV Voltage (V)	1000					
Rated DC Input Voltage (V)	620					
DC Input Voltage Range (V)	150-1000					
MPPT Voltage Range (V)	150-850					
Full MPPT Range(V)	500-850					
Start-up Voltage (V)	160					
Max. DC Input Current (A)	20x2	20+32	32x2		40x2	
Max. Short Current(A)	30x2	30+48	48x2		60x2	
No. of MPPT Tracker / Strings	2/2	2/3	2/4		2/4	
Battery Port						
Battery Nominal Voltage (V)	450	500	400	500	500	550
Battery Voltage Range (V)	150-800					
Max. Charge/Discharge Current (A)	30	50	50	50	60	60
Max. Charge/Discharge Power (kW)	12	15	17	20	25	30
Charging Curve	3 Stages					
Compatible Battery Type	Li-ion / Lead-acid / Sodium metal chloride battery					
AC Grid						
Nominal AC Output Power (kW)	12	15	17	20	25	30
Max. AC Input/Output Power (kVA)	18 / 13.2	22.5 / 16.5	25.5 / 18.7	30 / 22	37.5 / 27.5	45 / 33
Max. AC Output Current (A)	21.5	27	30	32	40	48
Nominal AC Voltage (V)	230/400					
Nominal AC Frenquency (Hz)	50/60					
Power Factor	1 (-0.8-0.8 adjustable)					
Current THD (%)	<3%					
AC Load Output (Back-up)						
Nominal Output Power (kVA)	12	15	17	20	25	30
Nominal Output Voltage (V)	230/400					
Nominal Output Frequency (Hz)	50/60					
Nominal Output Current (A)	17.4	21.8	24.7	29	36.3	43.5
Peak Output Power	13.2kVA, 60s	16.5kVA, 60s	18.7kVA, 60s	22kVA, 60s	27.5kVA, 60s	33kVA, 60s
THDV (with linear load)	<3%					
Switching Time (ms)	<10					
Efficiency						
Europe Efficiency	97.50%		97.80%		98.00%	98.10%
Max. Efficiency	98.30%				98.50%	
Battery Charge/Discharge Efficiency	98.00%					
Protection						
Reverse Polarity Protection	Yes					
Over Current / Voltage Protection	Yes					
Anti-islanding Protection	Yes					
AC Short-circuit Protection	Yes					
Leakage Current Detection	Yes					
Ground Fault Monitoring	Yes					
Grid Monitoring	Yes					
Enclosure Protect Level	IP65					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	558 x 535 x 260 mm					
Weight (kg)	29kg			36kg		
Topology	Transformerless					
Cooling Concept	Intelligent Fan					
Relatively Humidity	0-100%					
Operating Temperature Range (°C)	-25 to 60 °C					
Operating Altitude (m)	<4000					
Standby Consumption (W)	<5					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	NRS097, G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1					
EMC	EN61000-6-2, EN61000-6-3					

Three Phase Hybrid Storage Inverter

36-60 kW



The Afore AF series three phase storage inverters are designed to increase energy independence for homeowners and commercial users. The power range is from 36kW to 60kW, compatible with high voltage (150-800V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.

AI EMS

Electricity Pricing & Automation

BATTERY

Support
Sodium metal chloride battery

WIDE RANGE

Voltage Range
(150-800V)

100% UNBALANCE

Support Unbalance Load

MAX. 40A

String Current Up To 40A

<10ms

UPS FUNCTION
Switch Time < 10ms

INPUT

Support Generator

Support 280AH, 315AH battery system

Support for Time-of-use Optimization

Configurable Operation Modes

AFCI (Optional) & Rapid Shutdown Ready

2 times AC Oversize

Build in Anti-feed-in Function

100% unbalanced output, each phase

Smart Monitoring & Remote Firmware Upgrade

Technical Data	AF36K-TH	AF40K-TH	AF45K-TH	AF50K-TH	AF60K-TH
PV Input					
Max. DC Input Power (kW)	54	60	67.5	75	90
Max. PV Voltage (V)	1000				
Rated DC Input Voltage (V)	620				
DC Input Voltage Range (V)	150-1000				
MPPT Voltage Range (V)	150-850				
Full MPPT Range(V)	500-850				
Start-up Voltage (V)	160				
Max. DC Input Current (A)	40x 4				
Max. Short Current(A)	48x 4				
No. of MPPT Tracker / Strings	4/8				
Battery Port					
Battery Nominal Voltage (V)	500				
Battery Voltage Range (V)	150-800				
Max. Charge/Discharge Current (A)	120				
Max. Charge/Discharge Power (kW)	36	40	45	50	60
Charging Curve	3 Stages				
Compatible Battery Type	Li-ion / Lead-acid / Sodium metal chloride battery				
AC Grid					
Nominal AC Output Power (kW)	36	40	45	50	60
Max. AC Input/Output Power (kVA)	54 / 39.6	60 / 44	67.5 / 49.5	75 / 55	90 / 66
Max. AC Output Current (A)	60.5	67	75.5	83.5	96
Nominal AC Voltage (V)	230/400				
Nominal AC Frenquency (Hz)	50/60				
Power Factor	1 (-0.8-0.8 adjustable)				
Current THD (%)	<3%				
AC Load Output (Back-up)					
Nominal Output Power (kVA)	36	40	45	50	60
Nominal Output Voltage (V)	230/400				
Nominal Output Frequency (Hz)	50/60				
Max. AC Output Current (A)	60.5	67	75.5	83.5	96
Peak Output Power	39.6kVA, 60s	44kVA, 60s	49.5kVA, 60s	55kVA, 60s	66kVA, 60s
THDV (with linear load)	3%				
Switching Time (ms)	<10				
Efficiency					
Europe Efficiency	98.20%	98.30%	98.30%	98.30%	98.30%
Max. Efficiency	98.60%				
Battery Charge/Discharge Efficiency	99.00%				
Protection					
Reverse Polarity Protection	Yes				
Over Current / Voltage Protection	Yes				
Anti-islanding Protection	Yes				
AC Short-circuit Protection	Yes				
Leakage Current Detection	Yes				
Ground Fault Monitoring	Yes				
Grid Monitoring	Yes				
Enclosure Protect Level	IP66				
AC/DC surge protection	Type II				
General Data					
Dimensions (W x H x D, mm)	867 x 715 x 306 mm				
Weight (kg)	81kg				
Topology	Transformerless				
Cooling Concept	Intelligent Fan				
Relative Humidity	0-100%				
Operating Temperature Range (°C)	-25 to 60 °C				
Operating Altitude (m)	<4000				
Standby Consumption (W)	<100				
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec				
Certification & Approvals	NRS097, G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2				
EMC	EN61000-6-2, EN61000-6-4				