
Quality Maker®

Restarsolar, power the life

GLOBALPROFESSIONAL PV PRODUCTS INTEGRATED SOLUTIONS SUPPLIER



WWW.RESTARSOLAR.COM


RTM330M

60 Cells
Mono 4*9, 182*210mm


330W
Power output

21.87%
The Highest Efficiency

0~+5W
Tolerance



0.5% Annual Degradation over 30 years



LINEAR PERFORMANCE WARRANTY

12 Year Product Warranty

30 Year Linear Power Warranty

RTM330M

RTM330M HALF-CELL series is produced with high efficiency multi-busbar cells, which can reduce the module internal power loss to improve its conversion efficiency, as well as lower the failure risk caused by cracks and broken busbar to enhance the module reliability. Combined with half-cell technology, the module is highly resistant to hot-spot crisis caused by shadow effect.

High Reliability
Multi-busbar technology can effectively reduce the reliability risk caused by cells cracks and broken busbar.

Anti-PID Resistance
Prominent anti-PID performance reduces the power degradation, leading to higher energy yield and lower LCOE.

Durability Against Extreme Conditions
Certified to resist high salt mist and ammonia conditions.

High Efficiency
Multi-busbar technology can reduce the module internal power loss to improve the module conversion efficiency significantly.

Low-Light Performance
With high transmittance and anti-reflective 3.2mm tempered glass,the module has stronger performance under low light circumstances.

High Mechanical Strength
Certified to withstand: high wind load(2400Pa) and snow load(5400Pa).

Full range of products and certification systems

ISO 9001/14001 TUV PID-FREE CE IEC 61215/61730/61701/62716

Quality Maker®


Restarsolar, power the life


RTM330M

WWW.RESTARSOLAR.COM

GLOBALPROFESSIONAL PV PRODUCTS INTEGRATED SOLUTIONS SUPPLIER


Dimension of PV Modules Unit: mm






Back

Current-Voltage Curve



Power-Voltage Curve



ELECTRICAL DATA(STC)

Rated Power in Watts-Pmax(Wp)	330
Open Circuit Voltage-Voc(V)	25.20
Short Circuit Current-Isc(A)	16.79
Maximum Power Voltage-Vmp(V)	20.84
Maximum Power Current-Imp(A)	15.84
Module Efficiency	21.87%

STC: Irradiance 1000 W/m², Cell Temperature 25°C,Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA(NOCT)

Maximum Power-Pmax(Wp)	246.26
Open Circuit Voltage-Voc (V)	23.61
Short Circuit Current-Isc(A)	13.57
Maximum Power Voltage-Vmp(V)	19.41
Maximum Power Current-Imp(A)	12.69

NOCT: Irradiance at 800 W/m²,Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar cells	Mono-crystalline 182*210mm， Multi Bus bars
Cell configuration	36cells(4*9)
Module dimensions	1960*770*30mm
Weight	15.84kg
Front Cover	3.2mm Tempered Glass
J-BOX	IP68
Cable	4mm²(IEC)/12AWG(UL),900mm
Connectors	MC4 or MC4 Comparable

TEMPERATURE & MAXIMUM RATINGS

Nominal Operating Cell Temperature(NOCT)	45°C±2°C
Temperature Coefficient of Voc	-0.32%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.39%/°C
Operational Temperature	-40~+85°C
Maximum System Voltage	1500V(IEC)/1500V(UL)
Max Series Fuse Rating	20A
Limiting Reverse Current	20A

PACKAGING CONFIGURATION

Number of modules per container	
Package	
Package Number	

Address:Room 606,No.13,Yongshang Garden,Jinfeng Road, Mudu Town,Wuzhong District,Suzhou,Jiangsu Province,China
E-mail:info@resunsolar.com
Tel:+86 512-66292101

MADE IN CHINA