
Quality Maker®
Restarsolar, power the life

GLOBALPROFESSIONAL PVPRODUCTS INTEGRATED SOLUTIONS SUPPLIER



WWW.RESTARSOLAR.COM


RT8H-M-DG

132 Cells
Mono Topcon 16 BB


600-635W
Power output

23.51%
The Highest Efficiency

0~+5W
Tolerance



0.5% Annual Degradation over 30 years



LINEAR PERFORMANCE WARRANTY

15 Year Product Warranty
30 Year Linear Power Warranty

RT8H-M-DG

RT8H-M-DG HALF-CELL series is produced with high efficiency multi-busbar cells, which can reduce the module internal power loss to improve its conversion efficiency as well as lower the failure risk caused by cracks and broken busbar to enhance the module reliability. Combined with half-cell technology, the module is highly resistant to hot-spot crisis caused by shadow effect.

High Reliability
Multi-busbar technology can effectively reduce the reliability risk caused by cells cracks and broken busbar.

Anti-PID Resistance
Prominent anti-PID performance reduces the power degradation, leading to higher energy yield and lower LCOE.

Durability Against Extreme Conditions
Certified to resist high salt mist and ammonia conditions.

High Efficiency
Multi-busbar technology can reduce the module internal power loss to improve the module conversion efficiency significantly.

Low-Light Performance
With high transmittance and anti-reflective 2.0+2.0mm tempered glass,the module has stronger performance under low light circumstances.

High Mechanical Strength
Certified to withstand: high wind load(2400Pa) and snow load(5400Pa).

Full range of products and certification systems

ISO 9001/14001 TUV PID-FREE CE IEC 61215/61730/61701/62716


Quality Maker®
Restarsolar, power the life

RT8H-M-DG

WWW.RESTARSOLAR.COM

GLOBALPROFESSIONAL PVPRODUCTS INTEGRATED SOLUTIONS SUPPLIER

Dimension of PV Modules Unit: mm



ELECTRICAL DATA(STC)

Rated Power in Watts-Pmax(Wp)	600	605	610	615	620	625	630	635
Open Circuit Voltage-Voc(V)	48.30	48.50	48.70	48.90	49.10	49.30	49.50	49.70
Short Circuit Current-Isc(A)	15.73	15.78	15.83	15.88	15.93	15.98	16.03	16.08
Maximum Power Voltage-Vmp(V)	40.38	40.58	40.78	40.98	41.17	41.37	41.56	41.76
Maximum Power Current-Imp(A)	14.86	14.91	14.96	15.01	15.06	15.11	15.16	15.21
Module Efficiency	22.21%	22.40%	22.58%	22.77%	22.95%	23.14%	23.32%	23.51%

STC: Irradiance 1000 W/m², Cell Temperature 25°C,Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA(NOCT)


Maximum Power-Pmax(Wp)	457	461	465	469	473	477	481	485
Open Circuit Voltage-Voc (V)	45.26	45.44	45.63	45.82	46.01	46.19	46.38	46.57
Short Circuit Current-Isc(A)	12.71	12.75	12.79	12.83	12.87	12.91	12.95	12.99
Maximum Power Voltage-Vmp(V)	37.88	38.06	38.25	38.44	38.62	38.81	38.98	39.17
Maximum Power Current-Imp(A)	12.07	12.11	12.16	12.20	12.25	12.29	12.34	12.38

NOCT: Irradiance at 800 W/m²,Ambient Temperature 20°C, Wind Speed 1m/s.


INEGRATED PWER @ STC (REFRENCE TO 10%)

Maximum Power-Pmax(Wp)	660	665	671	676	682	688	693	698
Open Circuit Voltage-Voc (V)	48.30	48.50	48.70	48.90	49.10	49.30	49.50	49.70
Short Circuit Current-Isc(A)	17.30	17.35	17.41	17.46	17.52	17.58	17.64	17.70
Maximum Power Voltage-Vmp(V)	40.38	40.58	40.78	40.98	41.17	41.37	41.56	41.76
Maximum Power Current-Imp(A)	16.34	16.39	16.45	16.50	16.57	16.63	16.67	19.94
Module Efficiency	24.43%	24.62%	24.84%	25.03%	25.25%	25.47%	25.66%	25.84%
BNPI/Isc(BSI)	19.51	19.57	19.63	19.69	19.75	19.82	19.88	19.94

I-V CURVES OF PV MODULE



P-V CURVES OF PV MODULE



MECHANICAL DATA

Solar Cells	Mono-crystalline 182*105mm,16/Busbars
Cell Configuration	132cells(6*22)
Module Dimensions	2382 * 1134 * 35 / 30mm
Weight	32.9 / 32.4kg
Front Cover	2.0+2.0 mm Tempered Glass
J-Box	IP68
Cable	4mm²(IEC)/12AWG(UL),300mm+300mm, or customized
Connectors	MC4 or MC4 Comparable

TEMPERATURE & MAXIMUM RATINGS

Nominal Operating Cell Temperature(NOCT)	45°C±2°C
Temperature Coefficient of Voc	-0.25%/C
Temperature Coefficient of Isc	0.04%/C
Temperature Coefficient of Pmax	-0.29%/C
Operational Temperature	-40~+85°C
Maximum System Voltage	1500V(IEC)/1500V(UL)
Max Series Fuse Rating	25A
Limiting Reverse Current	25A

PACKAGING CONFIGURATION

	40HQ
Number of modules per container	620/740 pcs
Package	31/37 pcs/pallet
Package Number	20 pallets
Package Weight	1065/1243 kg/pallet
Package Dimension	2390*1130*1270 mm/pallet

Add: NO.99 ZHIDONG RD, ZHIXITOWN, JINTAN DISTRICT, CHANGZHOU,JIANGSU, CHINA
Tel: +86 512-66292101
E-mail: sales@restarsolar.com
Web: www.restarsolar.com